

Fasson® PPNg Top Silver/S692N/BG40 Wht (Imp.)

Spec# / BW0148

Last Modified: 18-Mar-2010

Facestock

A bi-axially oriented, glossy bright metallised polypropylene film with a print-receptive top coating.

Basis Weight 47 g/m² TAPPI T410
Caliper 52 µm TAPPI T411

Adhesive

S692N is a general-purpose permanent, emulsion acrylic adhesive.

Typical Performance Data

Initial Tack 10.7 N/25mm FTM 9 glass
Peel Adhes. 90° 8.8 N/25mm FTM 2 st.st.

Min. appl. temp. 5°C
Service temp. -20°C to 80°C subject to facestock limitations

Food Industry Labels

The adhesive complies with FDA regulations (section 175.105) for indirect food contact.

Liner

BG40 is a high density glassine paper featuring high internal strength, toughness and tear resistance as well as high transparency.

Basis Weight 62 g/m² TAPPI T410
Caliper 55 µm TAPPI T411

Laminate

ERROR: Entry not found in index or view's index not built	ERROR: ERR Entry not found in index or not view's foun index not d in built index or view' s index not built	ERROR: Entry not found in index or view's index not built
ERROR: Entry not found in index or view's index not built	ERROR: ERR Entry not found in index or not	ERROR: Entry not found in index or view's index not built

Applications and Uses

Applications include labeling of quality products such as cosmetics, toiletries, luxury articles and promotional labeling as well as automotive lubricants and household chemicals requiring durability and resistance to moisture or chemicals.

This product is ideal for applications requiring 'substrate identical labeling' on polypropylene containers and in environmentally sensitive markets requiring recycling of 'polyolefin' packs. Product can be used as a cost effective alternative to metallic foil blocking and shows good chemical and water resistance.

Due to fairly rigid nature of the film care should be taken with use on non-uniform surfaces or highly squeezable applications.

Printing / Converting

The modified acrylic based top coating allows printing by the usual printing technologies including letterpress, flexo, gravure and screen printing, giving good results with solvent, UV curing and water based inks. In case solvent screen inks are used, please consult your ink manufacturer. Good acceptance of hot foil blocking.

Material shows excellent register stability on press and excellent flat bed conversion while rotary and magnetic dies need additional care. Square corners should be avoided.

Shelf Life

One year when stored at 22°C and 50% R.H.

Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

view's found
index not found in
built index
or
view's
index
not
built

ERROR: Entry not
found in index or
view's index not
built

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's index not
built

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's index not
built

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's index not
built

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

ERROR: Entry not
found in index or
view's found
index not found in
built index

view'
s
index
not
built



Avery Dennison (Thailand) Ltd.
Avery Dennison Singapore Pte. Ltd.
P.T. Avery Dennison Indonesia
Avery Dennison Materials Sdn. Bhd.
ADC Philippines Inc.
Avery Dennison (Vietnam) Limited

Tel: +66 2 750 2070 Fax: +66 2 750 2071
Tel: +65 6349 0333 Fax: +65 6278 2455
Tel: +62 21 893 6033 Fax: +62 21 893 6031
Tel: +60 3 8925 0901 Fax: +60 3 8925 0903
Tel: +63 2 916 6816 Fax: +63 2 682 8243
Tel: +84 8 3816 4639 Fax: +84 8 3816 4638

Warranty

Information concerning Products are based upon tests believed to be reliable but do not represent a guarantee or warranty. Products are provided on the basis that any Purchaser has independently determined the suitability of the Products and Purchaser's purposes. The Company warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year of delivery (but not afterwards), upon notification thereof within seven (7) days of such appearance and substantiation that the Products have been stored and applied in accordance with the Company standards, the Company shall within a reasonable period correct such defects by providing a suitable replacement without charge at the Company's plant or at the location of the Products (at the Company's election) provided however, if the Company in its sole discretion determines that replacement is not commercially practical, the Company may issue a credit in favour of the Purchaser in an amount not to exceed the purchase price actually paid for the Products. Any implied warranty of merchantability fitness for particular purpose or other warranty of quality, whether express or implied by law, is hereby excluded to the extent permitted by law. In no event shall the Company be liable for any incidental, indirect or consequential damages including, but not limited to, loss of profit, loss of use or loss of capital. The remedies of the Purchaser set forth herein are exclusive, and the total potential liability of the Company arising out of any contract of or from the manufacture, sale, delivery, resale, installation or use of any products shall not exceed the purchase price of the products upon which liability is based.