




GT408e 203 dpi
GT412e 305 dpi
GT424e 609 dpi



High Performance Industrial Printer | GTe Series



Powerful. Intelligent. Reliable.



Field Installable Printheads for Quick Resolution Changes



Icon-Driven Operating System for Easy Operation



Multi-Function Operation Keys for Flexible Programming



Print Speed Up to 12 ips

Streamlined Features

- Industry Leading Throughput
- 4.1" Wide Print Area
- Up to 12 ips Print Speed
- User Changeable Print Resolution (203/305/609 dpi)
- RFID Ready
- Plug-In Interface Modules

Industry Verticals

- Automotive
- Food Services
- Distribution
- Government
- Logistics
- Manufacturing
- Wholesale

Industry Applications

- Compliance Labeling
- Service Bureaus
- Shipping/Receiving
- Asset Tracking
- WMS
- Logistic Tracking





GENERAL SPECIFICATIONS

GT408e | GT412e | GT424e

PRINTER MODEL		GT408e	GT412e	GT424e
PRINT SPECIFICATIONS				
Printing Method		Direct Thermal/Thermal Transfer		
Print Resolution		203 dpi (8 dots/mm)	305 dpi (12 dots/mm)	609 dpi (24 dots/mm)
Printing Speed		Up to 12 ips	Up to 12 ips	Up to 6 ips
Maximum Print Area	Width	4.1" (104 mm)		
	Length	98.43" (2,500 mm)	59.10" (1,500 mm)	15.7" (400 mm)
MEDIA SPECIFICATIONS				
Sensor Type		Reflective Sensor (for use with pre-printed marks) Adjustable See-Through Sensor (for die-cut label with gap)		
Media Type		Roll and Fanfold: 0.002" – 0.011" (0.06 mm – 0.268 mm)		
Media Size	Width	0.87" - 5.04" (22 mm - 128 mm)		
	Length	0.24" - 49.17" (6 mm - 1249 mm)	0.24 - 32.8" (6 mm - 833 mm)	
	Thickness	Up to 0.011" (0.268 mm)		
	Outer Diameter	10.43" (265 mm)		
	Core Diameter	1.5", 3" or 4" (38 mm, 76 mm or 102 mm)		
Ribbon	Width	1.56" - 5.04" (39.5 mm - 128 mm)		
	Length	Up to 1476' (450 m)		
MEMORY				
Processor		32-bit RISC		
Flash ROM		6 MB (Main Memory: 4 MB; Font: 2 MB)		
FONT/SYMBOLOGIES				
Fonts	Internal	U, S, M, WB, XS, XU, XM, XB, XL, OUTLINE, OCR-A, OCR-B, WL		
	TrueType	CG Times, CG Univers, Futura, CG Palacio, CG Century Schoolbook, CG Triumvirate Condensed		
Barcode Symbolologies	Linear	UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet™, GS1-128, GS1-DataBar™		
	2-D	PDF417, Micro PDF417, Truncated PDF417, Maxicode™, Data Matrix, QR Code, Composite Symbology		
INTERFACE CHARACTERISTICS				
Interface Buffer		2.95 MB		
Interface Options		Wireless Ethernet (802.11g), LAN (10/100BaseT), Centronics Parallel, EXT (14pin or 25pin) RS232C, IEEE1284 (ECP Compatible), RS422/485, 802.11G wireless		
OPERATING CHARACTERISTICS				
Power Requirements		100 - 240VAC [Maximum: 200VA/200W (Standby: 62VA/89W)]		
Environment	Operating	32° F – 104° F (0° C – 40° C), 30%-80% RH, non-condensing		
	Storage	23° F – 140° F (-5° C – 60° C), 30%-90% RH, non-condensing		
Regulatory Approvals		FCC Class A, UL, CSA, CE, TÜV, CCC		
Dimensions		17.9" (455 mm) L x 10.7" (271 mm) W x 12" (305 mm) H		
Weight		33.0 lbs. (15.0 kg)		
OTHER				
Firmware Features		Hex Dump, Print Custom Character Design, Sequential Numbering (incl. Barcodes), Form Storage and Recall (for faster data retrieval of complex formats)		
Self Diagnosis Tools		Head Check, Paper End Detection, Ribbon Near-End/End Detection (remaining 49' - 98' detection), Open Cutter-Cover Detection, Auto Sensing for Continuous Forms, Memory Card Error Detection, Test Print		
Optional Accessories		Label Cutter, Label Dispenser, Real Time Calendar/Clock, Linerless Kit		

SATO AMERICA, INC.
CORPORATE
 10350-A Nations Ford Rd
 Charlotte, NC 28273
 Phone: (704) 644-1650
 Fax: (704) 644-1662
 satosales@satoamerica.com

LABEL MANUFACTURING, SERVICE & SALES
 UNITED STATES MEXICO CENTRAL AMERICA
 CANADA CARIBBEAN

www.satoamerica.com

©2014 SATO America, Inc. All rights Reserved. Rev H • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.